Technical Specification


Machine model	Cardsmark
Card Material	PVC, Paper
Card size	(L)45~100×(W)40~120×(T)0.3~1.2 mm
Labeling Speed	20,000 cards/hour (CR80 card) (depend on printing data and inspection speed)
Hot-stamp Speed	15,000 cards/hour (CR80 card) (depend on the compatibility of card and card material)
UV ink printing Speed	12,000 cards/hour (CR80 card)
Inkjet Printing Inspection	26~45 digits/code Error I (missed fault) < 1 per mil. Error II (mis-reject)< 2%
Labeling Precision	±1mm(along movement direction) ±0.5mm(across movement direction)
Scratch-off coverage inspection	Positioning error (> +/- 1.5 mm) Inspection reliability > 99%
Power Consumption	220VAC 50Hz 3.5kW Air 0.6 Mpa
Environment	Ambient temperature 5~50 °C Relative Humidity 15~90% (w/o condensation)
Weight	Approximately 1,000 Kg (subject to options selected)
Dimensions	Approximately (W)0.76 x (L)7.496 x (H) 2.0 m (subject to options selected)

(Different functional modules are available for customer's special needs.)









For continuous improvement on design and product innovations, all specification data are subject to change without prior notice

Colamark (Guangzhou) Labeling Equipment Limited

19 Jin Xiu Road, GETDD, Guangzhou, China

Tel: +86 20 8221 6718 Fax: +86 20 8221 5799 PC:510730

Colamark Technologies Limited 820 Topsail Plaza,11 On Sum Street, Shatin, Hong Kong Tel: +852 2634 8011 Fax: +852 8161 3311 Email: info@colamark.com Web: www.colamark.com | Hong Kong | Guangzhou | Shanghai | Beijing | Shenyang | Qingdao | Wuhan | Chengdu | Kunming |

Colamark



Colamark · Cardsmark **Card Personalization System**



1 Control Program

Receives and encrypts the input database, downloads data to the inkjet printers for printing, maintains a log of printed data, and records data on the rejected cards, as well as generates opeartion records and managenment reports



2 Feeding Module

Comes with horizontal card loader, a separation and feeding mechanism with transport conveyor, thickness and length detection and rejection box

Comes with a module cabinet with transport conveyor and cover, inkjet printer mounting for 3 printheads, or up to 8 upon the requirement. (inkjet printers quoted separately)

cover, an inspection station with OCR high resolution camera, lighting and rejection device

Card Smark is a modular system for the personalization of cards with PINs. The system feeds cards, inkjet or laser prints the cards for personalized information and PINs, inspects the printed data, covers the PINs with a scratch panel, and collect the cards properly, all steps in one pass.

Cardsmark is equipped with powerful data processing capability for personalization data; characterized with outstanding performance, high throughput capacity, and flexible configuration.